



### Three- Door Desiccator Cabinet- Clear Acrylic , 24"x24"x36"



**Price:** RFQ

**Product Code:** 1500-3-J

**Manufacturer:** CLEATECH LLC

**Made in:** U.S.A

**Lead-time** Usually ship in 2-3 week

**Description:** 1500 Series Nitrogen purge desiccator cabinet with a heavy duty construction, airtight revolutionary door designs with one-piece gasket, stainless steel door frame, chambers for uniform gas distribution and particle from the air. Clear PVC is a good choice for operations with many corrosive chemicals.

#### Standard Features:

- Desiccator Overall Dimensions 24"Wx24"Dx36"H
- Material ¼" Thickness Clear Acrylic. It can be damaged by Alcohol and some cleaning agents, *except back plenum removable panel*
- Stainless steel door frame and stainless Steel door hinge
- Chrome Plated Wire Rack for Shelving, one pair per chambers (Optional if there is no shelf)
- Chrome plated Lift-and-turn Latch.
- Santoprene one-piece sealing.
- Opening of the door measures 22 ½"W x 10 3/16"H
- Internal usable space 22 1/8"Dx 11 11/16"H

#### Standard Options:

- Gas-in Port & Pressure Relief Valve (¼" OD tubing fitting)
- One-Channel Automatic Purge Control Unit (PCU) with one humidity sensor.
- Flowmeter, range 2-20 SCFH air. With Valve-External Mount (Not required if order PCU)
- Big Digit Hygrometer/ Thermometer (Temp. rang: 140° F , humidity range: 10% to 99 % RH).
- Stand with Caster or leveling mount Epoxy Power Coated Steel
- Perforated Stainless Steel Shelf , Perforated Acrylic Shelf and (required wire racks for shelf placement
- Cam lock, same key / different key, installed for each door, price per door.
- Locking Bracket, For Cabinet Type B, One per door, Stainless Steel, for use w/ Pad-lock.
- Stainless steel bottom plate, installed on the bottom of each chamber.
- Eliminating the back plenum for application required isolated chambers

#### Package Info:

- Package Type: Crate
- Package Dimensions: 29"Wx30"Dx45"H
- Approximate Gross Weight: 115 lbs.