



Five Door Sliding Drawer Desiccator Cabinet - Amber Acrylic, 26x18x62



Price: RFQ
Product Code: 1520-5-H
Manufacturer: CLEATECH LLC
Made in: U.S.A
Lead-time Usually ship in 2-3 week

Description: 1520 Series Nitrogen purge desiccator cabinet with a heavy duty construction, with one-piece gasket, stainless steel door frame, removable plenum chambers for uniform gas distribution and particle from the air. Clear PVC is a good choice for operations with many corrosive chemicals.

Standard Features:

- Desiccator Overall Dimensions 26"x18"x62"
- Material ¼" Thickness UV Amber Acrylic.
- Acrylic can be damaged by alcohol and some cleaning agents.
- Stainless steel door frame and stainless Steel door hinge
- Chrome plated Lift-and-turn Latch.
- Santoprene one-piece sealing.
- 30 clear Polypropylene drawers.
- Drawer Dimensions: 10.25"Wx13.25"Dx3"H
- Door Opening: 24.5"Wx10.3125"H

Standard Options:

- Gas-in Port & Pressure Relief Valve (¼" OD tubing fitting)
- One-Channel Automatic Purge Control Unit (PCU) With one humidity sensor.
- Flowmeter with an external valve mount. Range 2-20 SCFH air. (Not required if you order a PCU)
- Big Digit Hygro-Thermometer (Temp. rang:140°F, Humidity Range:10% to 99% RH)
- Stand with Caster or leveling mount Epoxy Power Coated Steel
- Cam lock, same key / different key, installed for each door, price per door.
- Stainless Steel Locking Bracket for use with a pad-lock.
- Eliminating the back plenum for application required isolated chambers

Package Info:

- Package Type: Crate
- Package Dimensions: 32"Wx24"Dx71"H
- Approximate Gross Weight: 185 lbs.