



## Six Door Sliding Drawer Desiccator Cabinet - Amber Acrylic, 52x18x38



**Price:** RFQ  
**Product Code:** 1520-6-K  
**Manufacturer:** CLEATECH LLC  
**Made in:** U.S.A

**Lead-time** Usually ship in 2-3 week

**Description:** 1520 Series Nitrogen purge desiccator cabinet with a heavy duty construction, with one-piece gasket, stainless steel door frame, removable plenum chambers for uniform gas distribution and particle from the air. Clear PVC is a good choice for operations with many corrosive chemicals.

### Standard Features:

- Desiccator Overall Dimensions 52"x18"x38"
- Material ¼" Thickness UV Amber Acrylic.
- Acrylic can be damaged by alcohol and some cleaning agents.
- Stainless steel door frame and stainless Steel door hinge
- Chrome plated Lift-and-turn Latch.
- Santoprene one-piece sealing.
- 36 clear Polypropylene drawers.
- Drawer Dimensions: 10.25"Wx13.25"Dx3"H
- Door Opening: 24.5"Wx10.3125"H

### Standard Options:

- Gas-in Port & Pressure Relief Valve (¼" OD tubing fitting)
- One-Channel Automatic Purge Control Unit (PCU) With one humidity sensor.
- Flowmeter with an external valve mount. Range 2-20 SCFH air. (Not required if you order a PCU)
- Big Digit Hygro-Thermometer (Temp. rang:140°F, Humidity Range:10% to 99% RH)
- Stand with Caster or leveling mount Epoxy Power Coated Steel
- Cam lock, same key / different key, installed for each door, price per door.
- Stainless Steel Locking Bracket for use with a pad-lock.
- Eliminating the back plenum for application required isolated chambers

### Package Info:

- Package Type: Crate
- Package Dimensions: 58"Wx24"Dx47"H
- Approximate Gross Weight: 260 lbs.