



## High-Performance Ducted Fume Hoods, Vertical Rising Sash



**Price:** RFQ

**Product Code:** 1100-3-A

**Manufacturer:** CLEATECH LLC

**Made in:** U.S.A

**Lead-time** Usually ship in 8 weeks

**Description:** General-purpose high-performance Benchtop Fume Hoods by Cleatech®, Double wall design constructed with durable steel with chemical-resistant liners. Available with Automatic sash closing option, in three standard lengths, 48" ,60" and 72" and two standard internal depth 24" and 30"

Fume hoods are tested to comply with ASHRAE 110:1995 and EN14175-3 standards.

### Standard Features:

- Overall Dimensions: 48" W x 33.75" D x 54.5" H
- Overall Dimensions (Including Base cabinet): 48" W x 33.75" D x 89.5" H
- Internal Usable Space: 39" W x 24"D x 47"
- Gauge 16 durable steel construction
- Vertical rising temper glass Sash
- Chemical resistant interior liners
- Engineered slotted baffle system
- Aerodynamic airfoil
- Chemical resistant dished work surface Spill proof.
- Durable external mount LED lighting provide very energy efficient illumination
- Stainless steel 10" Duct collar
- Airflow Alarm to monitor face air velocity

### Standard Options:

- Base cabinet Standard for general purpose storage needs
- Acid and corrosive storage cabinet
- Flammable Steel base cabinets for Flammable environment
- Duplex power outlet GFCI
- Pre-plumed Remote service fixture for water, air and gas
- Open frame 35" High stand with leveling mount
- Fan switch and remote exhaust blower
- Automatic sash controller.
- Remote exhaust fan

### Package Info:

- Package Type: Crate
- Package Dimensions: 54" W x 40" D x 64" H
- Approximate Gross Weight: 350 lbs.