



## Single Door Desiccator Cabinet- Static Dissipative PVC , 24"x24"x12"



**Price:** RFQ

**Product Code:** 1400-1-0

**Manufacturer:** CLEATECH LLC

**Made in:** U.S.A

**Lead-time** Usually ship in 2-3 week

**Description:** Single Chamber portable desiccator. High Clearance all plastic desiccator. Could be put in refrigerators and freezers or benchtops. Easy-open swing -down doors with foam rubber build sealing. Adjustable-Friction hinge to adjust door opening speed. Shelf supports strip allow shelf placement at two-inch increments.

### Standard Features:

- Desiccator Overall Dimensions 24"Wx24"Dx12"H
- Material ¼" Thickness Static Dissipative PVC.
- Adjustable-Friction hinge
- Stainless steel spring latches
- Opening of the door measures 23 ½" W x 10 ¾"H
- Internal usable space 23 1/8"Dx 11 ¾"H

### Standard Options:

- Gas-in Port & Pressure Relief Valve (¼" OD tubing fitting)
- Gas-in Port & with Stopcock Valve Pressure Relief Valve.
- One-Channel Automatic Purge Control Unit (PCU) with one humidity sensor.
- Flowmeter, range 2-20 SCFH air. With Valve-External Mount (Not required if order PCU)
- Big Digit Hygrometer/ Thermometer (Temp. rang: 140° F , humidity range: 10% to 99 % RH).
- Small Digit Hygrometer/ Thermometer ( Temp. rang: 14° F to 140° F, Humidity range: 10% to 99% RH)
- Acrylic/ Static Dissipative PVC Perforated shelves.
- Re-regenerable Silica Gel desiccant Cartridge 2"x2"x1" Contains 45.5 gms of Indicating Silica Gel will turn from blue to pink when it needs to be regenerated-Read more about [Desiccant](#)

### Package Info:

- Package Type: Crate
- Package Dimensions: 28"Wx28"Dx18"H
- Approximate Gross Weight: 45 lbs.