



Compact Glove Box



Price: RFQ
Product Code: 2500-2-D
Manufacturer: CLEATECH LLC
Made in: U.S.A
Lead-time Usually ship in 2 weeks

Description: Glove ports are located on the sides to allow a compact size. Compact glove box is an enclosed chamber with large front access door. The tilt-up window provides convenient viewing and accessibility.

Available with and without gas ports. Inert gas such as nitrogen, argon can be used to control the oxygen and humidity level.

They're portable and lightweight that can be setup anywhere. Available in cleanroom-safe materials including clear Acrylic, Static dissipative PVC and polycarbonate.

Standard Features:

- ¼" Thickness Clear Polycarbonate glove box is a good choice for operations with many corrosive chemicals and alcohol.
- Overall dimensions (Main chamber): 16" Wx16.5"Dx16"H
- Lift-up front window with Clear Non-dissipative window allows easy parts transfer from inside the Glovebox. The door opening 14 ½"x12 5/8"
- Interior Dimensions 15 ½"Wx15 ½"Dx15.5"H
- Two 8" Diameter glove port with Stainless Steel clamp can be used with any 8" standard glove

Standard Options:

- Gas-in port push-to connect fitting and Gas-out bleeding valve
- Single cord or Multi-cord Air-Tight Cord Grips, for cord diameter .08" to 1.25" Ideal for power cord data & internet cables, USB, monitor & printer connectors.
- Flowmeter with adjusting valve 0 to 20 SCFH
- Dry box gloves or Bare hand entry (IRIS port)
- Automatic purge control unit with RH or O2 sensor
- Digital Hygrometer and thermometer (15% to 99% RH, Temperature accuracy: ±1.8 F, Humidity accuracy: ±5%)
- Re-generable Silica Gel desiccant Cartridge 2"x2"x1" Contains 45.5 mgs of Indicating Silica Gel will turn from blue to pink when it needs to be regenerated –Read more about [Desiccants](#)

Package Info:

- Package Type: Crate
- Package Dimensions: 22W"x22D"x22H"
- Approximate Gross Weight: 35 lbs.